
Interconnect Cables

Part Number-AA

A: Cable Length Option in feet

For the cables listed below, order in increments of 1.0 ft (305 mm).

Examples:

1 5 = 15 ft (4.57 m)

2 0 = 20 ft (6.10 m)

The following are standard lengths	
Feet	Metres (approx.)
6	1.8
8	2.4
10	3.0
12	3.6
15	4.5
17	5.0
20	6.0
25	7.6
30	9.0
33	10.0
50	15.2
99	30.0

NOTE: Non-standard/custom lengths can also be ordered at additional cost

130539

3-conductor shielded 18 AWG (1.0 mm²) cable with 3-socket plug and fluorosilicone elastomer boot at one end, terminal lugs at the other end. Minimum length of 2.0 ft (0.6 m), maximum length of 99 ft (30 m). A manual is available to assist with installation of this cable (part number 133080-01).

16925

3-conductor shielded 22 AWG (0.5 mm²) cable with 3-socket plug at one end, terminal lugs at the other end. Minimum length of 2.0 ft (0.6 m), maximum length of 99 ft (30 m).

16710

3-conductor shielded 22 AWG (0.5 mm²) armored cable with 3-socket plug at one end, terminal lugs at the other end. Minimum length of 3.0 ft (0.9 m), maximum length of 99 ft (30 m).

Accessories

127088-01

330400 and 330425 Accelerometer Operations Manual.

00531080

Mating connector for 330400 and 330425 Accelerometers.

37439-01

For use with serial numbers NOT preceded with the letter "G".

Mounting Base, ¼-28 to ¼-28. Reduces base strain sensitivity.

37439-02

For use with serial numbers NOT preceded with the letter "G".

Mounting Base, M8X1 to M8X1. Reduces base strain sensitivity.

43217

Accelerometer Mounting Kit used with extension part number 108576-01 and O-ring part number 04290422 to allow room for the 330400 or 330425 accelerometer.

(See separate datasheet, p/n 141630-01.)